

# Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 1000VA, Lithium-ion, Rack/Tower, 2U, 230V, 6x IEC C13 outlets, SmartConnect Port+SmartSlot, Short Depth, AVR, LCD

SMTL1000RMI2UC

## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead Time	Usually in Stock

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	800 W
Rated Power In Va	1000 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	6 IEC 60320 C13
Number Of Rack Unit	2U
Battery Type	Li-Ion (Lithium-Ion)
Provided Equipment	Installation guide Rack mounting support rails USB cable

## Complementary

Software Package	SmartConnect software for remote power monitoring feature availability varies by terms of use
------------------	---

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Battery Graph Comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended Runtime	0
Battery Recharge Time	3 h
Battery Design Life	8...10 year(s)

---

Battery Charger Power	79 W rated
-----------------------	------------

## General

---

Product Web Sub-Family	Cloud-enabled monitoring
------------------------	--------------------------

---

Redundant	No
-----------	----

## Physical

---

Colour	Black with silver front bezel
--------	-------------------------------

---

Height	8.6 cm
--------	--------

---

Width	43.8 cm
-------	---------

---

Depth	31.8 cm
-------	---------

---

Net Weight	16.3 kg
------------	---------

---

Mounting Preference	Lower
---------------------	-------

---

Mounting Mode	Rack-mounted
---------------	--------------

---

Usb Compatible	Yes
----------------	-----

## Input

---

Input Protection Type	Circuit breaker
-----------------------	-----------------

---

Input Voltage Limits	151...302 V adjustable 160...280 V
----------------------	---------------------------------------

---

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

## Output

---

Crest Factor	3 : 1
--------------	-------

---

Harmonic Distortion	Less than 5 %
---------------------	---------------

---

Maximum Configurable Power In Va	1000 VA
----------------------------------	---------

---

Maximum Configurable Power In W	800 W
---------------------------------	-------

---

Transfer Time	6 ms typical : 10 ms maximum
---------------	------------------------------

---

Ups Type	Line interactive
----------	------------------

---

Wave Type	Sine wave
-----------	-----------

---

Output Frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

## Conformance

---

Product Certifications	C-Tick CE EAC RCM
------------------------	----------------------------

---

Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

## Environmental

---

Acoustic Level	41 dBA
----------------	--------

---

Heat Dissipation	70 Btu/h
------------------	----------

---

Operating Altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature For Operation	0...40 °C
---------------------------------------	-----------

Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...7620.00 m
Ip Degree Of Protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

## Communications & Management

Alarm	Audible and visible alarms
Control Panel	Multifunction LCD status and control console
Free Slots	1
Communication Port Support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

## Surge Protection and Filtering

Surge Energy Rate	680 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	22.9 cm
Package 1 Width	47.2 cm
Package 1 Length	58.4 cm
Package 1 Weight	18.6 kg

## Logistical informations

Country Of Origin	PH
-------------------	----

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile** [End of Life Information](#)