



HX 7500 T

PORTABLE POWER

Generating Sets Range INTENS

PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- HONDA Professional Engine
- Solid and high-performance equipment

Range INTENS

Equipment that is robust, long-lasting and simple to use for repetitive operations in difficult conditions.



This product meets the Qualigen charter, which aims to ensure a high level of quality and guarantee the safety of users. Qualigen commitment to safety and quality.

HX 7500 T

GENERAL SPECIFICATIONS

Range	INTENS
Frequency (Hz)	50
Max power LTP (kW) *	6
Max power LTP (kVA)	7.50
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	6.10
75% cons. (l/h) *	2.50
75% Autonomy (h) *	2.40
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX390
Distribution	O.H.V.
Start	Starter
Low Oil pressure shutdown	Oui
Displacement (cm ³)	389
Oil capacity (L)	1.10

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	77
Width (cm)	57
Height (cm)	59
Dry Weight (kgs)	80

PACKAGING

Packaging type	Box
Length (cm)	78.50
Width (cm)	58
Height (cm)	59.50
Weight (kg)	82.50
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	192
weight of the packaged Pallet (kg)	505



ACCESSORIES SUPPLIED



Funnel



User and maintenance manual

OPTIONS



R03 **Diferential protection** This set includes the hour meter and the differential circuit breaker.



R07 **Trolley kit** Trolley kit for generating sets > 3 kW with a stretcher system for easy handling.



R19 **Maintenance kit** Maintenance kit for Honda GX390 engines (except Alizé 6000E and Alizé 7500 TE)



RH1 **Protection cover** Cover for SDMO 's generating sets, welding sets and water pumps



RPM **Set of male plugs** Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ **Earth spike** For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.