



## PERFORM 3000 TB UK

PORTABLE POWER

50Hz UK range Perform :

An efficient, cost effective and easy to handle generator suitable for frequent use.

### Product Advantages

- ➔ OHV KOHLER professional engine
- ➔ Solid and compact frame
- ➔ Rubber grip handles for comfort/Safety
- ➔ Rubber feet – minimising vibration/noise
- ➔ Extra HP in its power category
- ➔ Maintenance free alternator
- ➔ Thermal Overload Trip
- ➔ Compact frame with side panels for protection
- ➔ Oil Alert/Guard
- ➔ 3 x 16amp Dual voltage sockets
- ➔ Four stage engine air filter filtration

### Standard accessories

- ➔ Draining funnel
- ➔ User and maintenance manual
- ➔ Floor maintaining slot
- ➔ Ergonomic handle grip
- ➔ Thermal circuit breaker



### QUAD CLEAN AIR FILTER

The Cyclonic Quad Clean™ air filters provide 4 levels of filtration which effectively filter out large particles and capture the finest particles. They ensure a continuous supply of clean air to the engine increase the engine performance and extend its lifetime, reducing running costs.

## PERFORM 3000 TB UK

### General specifications

Range	Perform
Frequency (Hz)	50
Max. power (kW)	3
Max power. (kVA)	3.75
Nominal voltage (V)	230 / 115
Number of phase	Single phase
Acoustic pressure level Lw(A)	96
Noise level dB(A) - 1m	
Noise level dB(A) - 7m	68

### Engine specifications

Engine trademark	Kohler
Engine type	CH 270
Distribution	O.H.V.
Start	Recoil
Fuel	Unleaded Petrol
Autonomy (h)	3.2
Consumption (L/h]	1.3
Tank (L)	4.1
Oil Guard	Yes
Capacity (cm3)	208
Oil capacity (L)	0.6

### Alternator specifications

Type	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

### Plugs and panel descriptive

2 x 2P+T 115V 16A – Thermal breaker + 1 x 2P+T 230V 16A – Thermal breaker

### Dimensions and weight

Lenght (cm)	65
Width (cm)	51
Height (cm)	46
Dry Weight (kgs)	43

### Packaging

Packaging type	Box
Length (cm)	66
Width (cm)	52.5
Height (cm)	47
Pallet type	140/110
Number of box by pallet	12
Pallet height (cm)	150

The QUALIGEN charter/certification, defined by the SIMOTHERM and GIGREL professional organisations is an EEC quality mark, similar to British Standard kite mark. The QUALIGEN charter confirms the product achieves the highest standards, ensuring all the data offered is accurate (user safety, noise level, power, sales information, after sales service), confirming the equipment complies with all EEC current regulations guaranteeing the highest levels of quality are achieved in all our products and thus ensuring the users safety.

**Options**


<b>RKB1</b>	Trolley kit for the generating sets of 6kW or below
<b>RKS1</b>	10 maintenance kits for KOHLER CH270 engines
<b>R50</b>	16A blue 230V male plug - Sold per 1 or 10
<b>R51</b>	16A yellow 115V male plug - Sold per 1 or 10
<b>R55</b>	ADAPTOR R5516A/13A adaptor economy. Sold per 1 or 3
<b>R56</b>	ADAPTOR R5616A/13A double adaptor. Sold per 1 or 3
<b>RBH1</b>	Box of 20 x 1 L cans of oil (SAE 15W40)
<b>RBH0-5</b>	Box of 24 x 0.5L cans of oil (SAE 15W40)
<b>RHO</b>	Cover for SDMO generator sets and petrol or diesel driven pumps
<b>RPQ</b>	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm <sup>2</sup> cable.
<b>RBAC</b>	Removable storage box